

Part No.	Door Count	Description	Weight
<b>E8H</b>	8 - 12 Doors	Enclosure with main backplate	60 lbs

E8 enclosure size: 36H x 30W x 6.5D



### Overview


HCLASS multi-purpose enclosures offer maximum flexibility, functionality and savings to access system designers. HCLASS enclosures are engineered to house FlexPower® power management boards alongside Honeywell Pro-Watch® access panels in one compact, secure system. The E8H can be configured for a maximum of twelve doors with dual voltage distribution.

To prevent damage to system electronics, the backplate separates from the enclosure for access hardware mounting in the shop while wiring is pulled to the enclosure at the job site. Once configured, the backplate can be remounted for final ties and checkout.

### Features

- Mounts LSP power and access hardware in a variety of combinations
- Removable backplate simplifies job installation
- Protected AC input terminal - meets arc protection requirements
- AC on/off circuit breaker switch
- Pre-engineered access mounting pattern
  - ◆ Power and distribution boards are mounted and pre-wired
  - ◆ Access boards mount on provided threaded standoffs
- Mechanical upgrades
  - ◆ Removable door with quick disconnect grounding strap
  - ◆ 6.5" enclosure depth accommodates 12Ah battery sizes
  - ◆ Lock with two (2) keys and installed tamper switch
  - ◆ 16 Gauge steel with LSP black textured finish
  - ◆ Multiple knockouts all four sides

### Custom Backplate Mounting System



### Flexible Mounting Pattern


The E8H backplate is designed with a unique Honeywell mounting pattern to provide the installer with a configuration mechanism capable of supporting up to 12 doors with system and lock power in an extremely efficient manner. The backplate is removable and mounts controllers and LSP modules in both single and dual voltage configurations.

The E8H1 variant adds a door backplate for expansion of distribution modules or up to four more controllers (see E8H1 datasheet).

The 6.50" cabinet depth allows up to 12Ah battery sizes for greater standby time.

## E8H Honeywell Mounting Guide

Pro-Watch Panel	Available Slots
Controller	6
Reader	6
I/O	6



### Enclosure Features

#### ♦ Custom Backplate


- Light weight aluminum with AC and battery slots to protect cables
- LSP pre-wired power modules reduce installation time
- Front side screw in standoffs simplifies panel installation
- Wide wire management channels for panduit or tie wrap

#### ♦ Mechanical

- Protected AC cover with on/off circuit breaker for maintenance safety
- Pre-drilled mounting holes for easy field upgrades
- 6.5" cabinet depth accommodates large battery sets
- Removable door with "fast disconnect" ground strap
- Multiple knockouts all four sides

**E8 Mechanical Specification**

**E8 Enclosure Dimensions (H x W x D)**  
**36.00" x 30.00" x 6.50" (91 x 76 x 16.5 cm)**



**LifeSafetyPower.com**

(888) 577-2898  
 info1@LifeSafetyPower.com

Specifications subject to change without notice.

© 2025 LifeSafety Power. All rights reserved. LifeSafety Power and FlexPower are registered trademarks of LifeSafety Power. All other trademarks and copyrights are the property of their respective owners.

P01-766\_02 04/25

**LifeSafety Power**  
 10027 S. 51st Street, Suite 102  
 Phoenix, AZ 85044 USA

