


FLEXPOWER

GEN2 POWER SUPPLIES



Overview

FlexPower smart power supplies offer unique performance value with these standard features:

- **208 - 230VAC** - wide range input
- **TruWatt™** - same power output at 12 or 24V DC
- **FAI** - Fire alarm disconnect on a per output basis
- **Locksafe™** - voltage optimization for longterm lock protection
- **SureCharge™** - smart battery charger for SLA or LFP
- **Outsmart™** - bicolor output LED (12V/Green, 24V/Blue)
- **NetLink™** - built in network interface
- **DPM™** - RS485 interace for distributed power monitoring

Family Specifications

Input:

- 208 - 230VAC ±10%, 50/60Hz

Outputs:

- DC1 output continuous
- DC2 output switched on FAI Input
- Overload & short circuit protection with auto-restart

Battery Backup:

- Built-in microprocessor controlled smart charger
- Charges Sealed Lead Acid (SLA) or Lithium Iron Phosphate
- Auto switchover to battery with zero transfer time
- Integrated low battery cutoff

Supervision:

- AC fail, Battery fail, System fault (form "C")
- Low power shutdown when battery voltage too low

Fire Alarm Disconnect Activation:

- DC voltage: 9 to 33VDC, 3 to 15mA
- Dry contact NO/NC
- Optional Fire Alarm latching

LED visual indicators:

- AC input, DC output, system faults, fire alarm activation

Agency Approvals:

- IEC 62368-1:2014, EN55032:2015, EN61000-3-2:2014
- EN61000-3-3:2013, EN55024:2010 +A1:2015
- CE | UKCA | BIS IS13252(Part1):2010 | NOM 001:2018 | RCM, SAA
- UL294, UL1076 | ULC S319
- CSA C22.2 #107.1
- FCC Part 15 Subpart B
- CSFM approved | ROHS 3 Leadfree

Electrical Specifications

Power Supply Model No*	FPO75/E	FPO150/E	FPO250/E
Input Voltage	208 - 230 VAC ±10% 50/60Hz		
Input Current (max)	1.6A	2.5A	3.2A
12 VDC Output Current	6 Amp	12 Amp	20 Amp
24 VDC Output Current	3 Amp	6 Amp	10 Amp
Maximum Charge Current	1 Amp	2 Amps	
Maximum Battery Size	40Ah	80Ah	
Low Battery Disconnect	at 70% of battery voltage		
System BTU/Hr	33	66	109
Full Load Efficiency	83%	87%	88%
Operating Temperature	-4 to +122F (-20 to +50C)		
Board Size (inches)	4 x 6 x 2.5	5.5 x 8.25 x 2.5	
Board Weight	1 lb	2 lbs	

*For 110VAC models see FPO series datasheet

GEN2 ADVANCED FEATURES

LockSafe™ - optimized system and battery charge voltages
OutSmart™ - visual voltage verification technology
Dual mode charger - supports SLA or Lithium Iron Phosphate batteries
Built in low battery cutoff - prevents deep discharge
Built-in battery current sensor - for enhanced battery monitoring
Built-in output current sensor - monitors total power supply output
Network Management
RS485 - communication option for expanded network monitoring
DPM™ Distributed Power Monitoring - lower managed cost per output
AC line monitoring - remotely monitors AC line voltage
Primary output reset - cycles main output power remotely

FPO Series Power Supply/Chargers

FAI | RS485 | Network Ready | CE/RCM/UKCA/BIS/NOM/UL/CUL

FLEXPOWER STANDARD FEATURES

SureCharge® The microprocessor controlled constant current charging process used by the FPO power supply guarantees proper charging current for the battery and the fastest charge time without stress or damage to the battery.

VSelect® One single switch for configuring the output between 12 and 24VDC eliminates field errors and allows for the reduction and simplification of service inventory by eliminating the necessity of stocking units in each voltage.

TruWatt® Output power capability of the power supply remains constant regardless of the output voltage setting. For example, a FlexPower 250 watt supply will provide 10 amps at 24VDC and 20 amps at 12VDC, allowing the same number of locking devices to be used at either the 12 or 24V setting.

FlexConnect® Power supply and accessory board interconnection system uses common mounting footprints, predrilled mounting holes, snap-in standoffs, pluggable wires, and a dual buss distribution architecture to simplify installation and service.

DataLink® Key power functions are monitored and reported through PC or browser interface with the PowerCom management software.

GreenSmart® FlexPower systems are RoHs compliant, lead-free, and meet the latest state, federal and European requirements for energy efficiency.

NEW GEN2 FEATURES

LockSafe™ Voltage Optimization Independent battery charging circuit provides the proper charging voltage without overheating locks due to excessive output voltage.

OutSmart™ Visual Voltage Indication Dual color output LEDs indicate the output voltage setting: Green/12V or Blue/24V.

Smart Dual Mode Charger jumper selection for either Lithium Iron Phosphate or Sealed Lead Acid (SLA) batteries.

DPM™ Distributed Power Monitoring RS485 daughter board option allows up to 24 LSP devices to be monitored across a campus from a single network drop.

Remote Main Output Reset Allows remote shutdown of the main output voltage through NetLink to perform a full system reset.

Remote AC Line Monitoring Watches and reports AC line voltage connected to the FPO through NetLink. Programmable window limits allow customizable AC power alerts.

On-Board Low Battery Disconnect Automatically disconnects discharged battery sets to prevent deep discharge and protects sensitive electronics.

On-Board Battery Current Sensor Eliminates the need for an external battery sensor when used with NetLink, simplifying wiring and freeing up NetLink current sensors for other uses.

On-Board Output Current Sensor Reports the total output current being delivered by the FPO power supply through NetLink.

Product Ordering

To contact a local representative and place an order visit: www.lifesafetypower.com/about-us/where-to-buy or contact LSP to place an order:


LifeSafety Power LLC
10027 S. 51st Street, Suite 102
Phoenix, AZ 85044 USA

www.lifesafetypower.com
Phone (888) 577-2898
info@lifesafetypower.com

IMPORTANT

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. LifeSafety Power makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. LifeSafety Power's only obligations are those in the LifeSafety Power Standard Terms and Conditions of Sale for this product, and in no case will LifeSafety Power or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, LifeSafety Power reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.

FLEXPOWER PERFORMANCE GRAPHS



FLEXPOWER BOARDS

