





#### **ELECTRICAL RATINGS**

Parameter	Rating
Input Voltage	120 VAC, 50/60Hz
Input Power (max)	452W
Output Power	400W
Relay Lock Outputs	16 @ 3A Fused
Auxiliary Outputs	16 @ 3A Fused
Maximum Charge Current	FPO150: 2A, 80AH maximum
	FPO250: 2A, 80AH maximum
Low Power Disconnect	at 70% of battery voltage
Systems BTU/Hr	175 BTU/Hr
Operating Temperature	32 to 122F (0 to +50C)
Efficiency	87% 120VAC 60Hz In, Full Load
Agency Approvals	UL294, UL603, UL1076, ULC S318, ULC
	S319, CSA C22.2 #205, FCC Part 15,
	Subpart B, CSFM IEC 62368-1:2014,
	EN 55032:2015, EN6100-3-2:2014,
	EN6100-3-3:2013,
	EN55024:2010+A1:2015, BIS
	IS13252(Part 1):2010, REACH 209,
	ROHS 3

### **OVERVIEW**

AMAG Unified Power Systems combine FlexPower power modules alongside access control hardware in one compact and secure UL listed solution. Unified Power features include:

- · Built in Fire Alarm disconnect unlocks doors on a fire alarm
- · Low battery cutoff protects batteries from deep discharge
- · Dedicated fast charger prolongs battery life
- · Enhanced surge immunity for input/output protection
- Locksafe optimized voltages provide long-term lock protection
- OutSmart Visual LED notification (12V/Green, 24V/Blue)
- · Network ready with optional LifeSafety Power NetLink® module
  - o Monitor power supply and battery in NetLink dashboard
  - Remote test batteries
- · Lifetime Warranty LifeSafety Power's quality commitment

#### SYSTEM DETAILS

- . 1 x FPO150, 1 x FPO250 400W Total Output, 120 VAC Input, AC Fault and System Fault form C contacts may be triggered by low/no battery, short to earth ground, power supply failure, or
- . 2 x C8 (16 Relay Lock Outputs) 3A fused outputs, programmable for failsafe/failsecure, FAI, NC/NO input, voltage or dry output per zone. Dual buss voltage selection by zone, OutSmart dual color LEDs
- . 2 x D8 (16 Auxiliary Outputs) 3A fused Outputs, dual buss voltage selection by zone, OutSmart dual color LEDs
- E8A Enclosure Size: 36.0H x 30.0W x 6.5D in (91.44 x 76.20 x 16.51 cm)
  - Enclosure E8 E8 enclosure size 36H x 30W x 6.5D
  - o Backplate E8A Backplate mounting for M2150 and M4000 controllers
- System Weight 64.05 lbs (29.05kg)

## ORDERING

FPO150/250-2C82D8E8A

120 VAC, 400W, 16 Lock, 16 Aux

# **AGENCY LISTINGS**

US | Canada | Mexico | Europe | UK | India | Australia | New Zealand | RoHS

















LifeSafety Power Disclaimer: