



## Overview

MCLASS™ Unified Power Systems combine FlexPower® power modules alongside Mercury Security™ access hardware in one compact and secure UL Listed solution.

The FPO Power Supply / Battery Charger provides two power outputs user selectable for 12 or 24 VDC. One output provides continuous output power for system use, the second is resettable output power, activated when the fire alarm disconnect is initiated.

For access or lock power, the D8P provides eight class 2 power limited outputs rated at 2.5A per output, each individually programmable for constant output or FAI disconnect.

MCLASS enclosures are painted steel with removable backplate and include lock, two (2) keys and tamper switch.



## System Features

- ◆ **FPO offline power supply**
  - 120 or 230 VAC input
  - 12 or 24V DC outputs
  - On board Fire Alarm Interface
  - Continuous and resettable DC
- ◆ **Auxiliary outputs**
  - Eight, Class II power limited at 2.5A each
  - Each programmable to either continuous or resettable DC
- ◆ **Expansion options**
  - Increased power, multiple voltages
  - Additional distribution outputs
  - Network monitoring and reporting
- ◆ **Lifetime Warranty**

## Enclosure Features

- ◆ **Labor saving design**
  - Pre-wired power section
  - Pre-punched knockouts
  - Removeable backplate simplifies installs
  - Pre-defined hole pattern for power section
  - Access panels mount on threaded standoffs - no drilling required
- ◆ **Additional benefits**
  - Wire management room
  - 4.5" enclosure depth fits battery set
  - Tamper switch, lock, dual key set standard
  - Mounting hardware for access boards included

## Ordering

## Description

Ordering	Description
FPO75-D8PE2M	120VAC, 75W (12V or 24V) 8 Aux Class 2 outputs, 20x16x4.5 Encl.
FPO75-D8PE2M/E	230VAC, 75W (12V or 24V) 8 Aux Class 2 outputs, 20x16x4.5 Encl.



## Specifications


<b>Input Power</b>	Input 120/230 VAC 50/60 Hz   83 Watts (.70 Amps) Overload and short circuit protection Over temperature protection Polarized AC power supply disconnect
<b>Output Power</b>	FPO75: 12V/6A or 24V/3A   75 Watts Outputs: Continuous (DC1) Resettable (DC2) 8 auxiliary outputs, class II power limited rated at 2.5 Amps per output 120 mV output voltage ripple System Efficiency: 83%   System BTU Rating: 33 BTU/Hr
<b>Battery Charging</b>	Independent built-in 1A charger for sealed lead acid or gel type batteries Microprocessor dual rate charging of 12 or 24 V battery sets Charges up to 40Ah battery sets within UL limit Automatic switchover to standby battery when AC fails Zero voltage drop when switched over to battery backup
<b>Supervision</b>	AC Fail (form "C" contacts) System fail (form "C" contacts) may be triggered by low/no battery, short to earth ground, power supply failure or blown fuse
<b>Visual Indicators</b>	AC input, DC1 and DC2 output System fault   AC fault   Short to earth ground   Reverse battery polarity Fire Alarm Input activated D8P: DC outputs
<b>Regulatory Compliance</b>	UL294, UL603, UL1076, ULC S318, ULC S319
<b>Mercury/LSP</b>	CSA C22.2 #107.1, CSA 22.2 #60950
<b>Joint Listing</b>	CSFM / FCC Part 15, Subpart B CE
<b>Enclosure Dimensions</b>	Size: 20.00H x 16.00W x 4.50D in. (51.00 x 41.00 x 11.50 cm)   Weight: 18 lbs.
<b>Access Panel Mounting</b>	LP1501, LP1502/4502, LP2500, MR50, MR51e, MR52, MR16, LNL-500, 1100, 1200, 1300, 1320, 2000, 2210, 2220, 3300

**E2M Mercury Mounting Guide**

Mercury	Slots w/Power	Slots all Mercury
LP1502 / 4502	3	4
LP2500 / MUX8	3	4
MR16in / MR16out	3	4
MR50	1	1
LP1501 / MR51e	2	2

**Enclosure Features**

- ◆ **Custom Backplate**
  - LSP power modules pre-wired in top area
  - One LP1502 controller or up to two POE controllers
- ◆ **Mechanical**
  - 4.5" cabinet depth
  - Removable door with "fast disconnect" ground strap
  - Multiple knockouts all four sides
  - Network module mounting holes for field upgrade



**LifeSafetyPower.com**

(888) 577-2898  
 info@lifesafetypower.com

Specifications subject to change without notice.  
 © 2022 LifeSafety Power. All rights reserved. LifeSafety Power and FlexPower are registered trademarks of LifeSafety Power. This literature is for guidance only. It does not constitute recommendations, representation, or advice, nor is it part of any contract. Our policy is one of continuous product improvement, and the right is reserved to modify the specifications contained herein without notice.

P01-469A 06/22

**LifeSafety Power**  
 10027 S. 51st Street, Suite 102  
 Phoenix, AZ 85044 USA