

Mercury Helix Power Redundant Power Systems

Mercury Helix Redundant Power Systems combine our Mercury Unified Power systems with DC Helix redundant power for the highest reliability in mission critical applications.

Helix Unified Power Features

- Redundant DC power supply boards
- Available redundant AC power input
- Single enclosure solution reduces wall space requirements
- Single AC drop
- Removable backplate for easy installation
- Predrilled & tapped holes for access panel mounting
- Mounting hardware included
- Single or dual voltage, standard or network managed



title="Dynamic Link with Double Vertical Movement" 800" height="100" width="100" tab
DVM Managed, 8 Aux
DVM Managed, 8 Aux
[tab] [tab title="More Information"]
Type: UL334, E4M1
4M12V and 8M24V
4M12V and 8M24V
8 Managed, 8 Aux
Power: 4M
E4M
E4M

Agency Listings

- UL294 / UL603 / UL1076 / ULC S319 • CSA C22.2 #107.1 • FCC Part 15, Subpart B • IEC 62368-1:2014, EN55032:2015, EN61000-3-2:2014
- EN6100-3-3:2013, EN55024:2010 +A1:2015
- CE, UKCA, BIS IS13252(Part1):2010, NOM 001:2018, RCM, SAA
- CSFM Approved, ROHS 3 Lead Free

Documents

HLX-4DR-E4M	DS	IM	CAD	AG
HLX-4DRN-E4M	DS	IM	CAD	AG
HLX-8DR-E4M1	DS	IM	CAD	AG
HLX-8DRN-E4M1	DS	IM	CAD	AG

[/tab] {/jatabs}